



HEATING
PRODUCTS




- > CAST IRON RADIATOR
- > CAST IRON BOILER
- > GAS CONVECTOR
- > STEEL BOILER

COLUMN STYLE



MODEL	DIMENSIONS (mm)						Δt 50		Δt 60		
	COLUMNS	A HEIGHT	B TAPPING CENTERS	C DEPTH	D WIDTH	WATER CONTENT (L)	WEIGHT (KG)	Kcal/h	watts	Kcal/h	watts
4/28 Column Radiator	4	300	200	144	60	0,35	3,35	37	43	47	55
4/28 Column Radiator with Foot	4	357	200	144	60	0,35	3,91	37	43	47	55
4/45 Column Radiator	4	415	320	144	60	0,51	4,1	56	65	71	82
4/45 Column Radiator with Foot	4	475	320	144	60	0,51	4,66	56	65	71	82
4/65 Column Radiator	4	600	500	144	60	0,85	5,44	80	93	101	118
4/65 Column Radiator with Foot	4	660	500	144	60	0,85	6,11	80	93	101	118
4/75 Column Radiator	4	700	600	144	60	0,97	6,11	93	108	117	137
4/75 Column Radiator with Foot	4	760	600	144	60	0,97	6,74	93	108	117	137
4/95 Column Radiator	4	900	800	144	60	1,1	7,77	119	139	151	176
4/95 Column Radiator with Foot	4	960	800	144	60	1,1	8,23	119	139	151	176
6/48 Column Radiator	6	425	350	221	60	0,85	6,29	82	95	104	121
6/48 Column Radiator with Foot	6	485	350	221	60	0,85	6,93	82	95	104	121
6/65 Column Radiator	6	600	500	221	60	1,2	8,26	114	133	145	169
6/65 Column Radiator with Foot	6	660	500	221	60	1,2	8,8	114	133	145	169
6/75 Column Radiator	6	700	600	221	60	1,4	9,5	130	151	164	190
6/75 Column Radiator with Foot	6	760	600	221	60	1,4	10,05	130	151	164	190
6/95 Column Radiator	6	899	800	221	60	1,6	12,11	169	197	213	248
6/95 Column Radiator with Foot	6	960	800	221	60	1,6	13,1	169	197	213	248



PERCOLUMN STYLE



MODEL	DIMENSIONS (mm)						Δt 50		Δt 60		
	COLUMNS	A HEIGHT	B TAPPING CENTERS	C DEPTH	D WIDTH	WATER CONTENT (L)	WEIGHT (KG)	Kcal/h	watts	Kcal/h	watts
200 / 250	6	280	200	250	60	0,88	4,75	72	62	91	105
350 / 70	2	430	350	70	60	0,36	2,6	39	41	49	57
350 / 160	4	430	350	160	60	0,72	4,68	70	61	89	104
350 / 220	5	430	350	220	60	1	5,93	96	83	122	141
500 / 70	2	580	500	70	60	0,48	3,41	54	46	68	79
500 / 110	3	580	500	110	60	0,8	4,75	71	61	90	104
500 / 160	4	580	500	160	60	0,9	6,21	102	88	129	150
500 / 220	5	580	500	220	60	1,1	7,83	124	106	156	182
600 / 70	2	680	600	70	60	0,56	3,82	53	62	68	79
600 / 160	4	680	600	160	60	1,08	7,41	106	122	134	156
900 / 70	2	980	900	70	60	0,8	5,15	86	74	109	127
900 / 160	4	980	900	160	60	1,3	10,4	156	134	198	230
900 / 220	5	980	900	220	60	1,8	13,38	202	174	256	297

RIDEM STYLE



RIDEM STANDARD STYLE

MODEL	DIMENSIONS (mm)					WATER CONTENT (L)	WEIGHT (KG)	Δt 50		Δt 60	
	COLUMNS	A HEIGHT	B TAPPING CENTERS	C DEPTH	D WIDTH			Kcal/h	watts	Kcal/h	watts
2/813	2	885	813	62,4	60	0,71	5,23	72	84	91	106
3/350	3	422	350	98,2	60	0,56	3,9	50	58	63	73
3/500	3	572	500	98,2	60	0,72	4,61	66	77	84	97
3/623	3	699	623	98,2	60	0,8	5,94	78	91	99	115
3/813	3	885	813	98,2	60	1,1	7,27	96	112	122	142
4/500	4	572	500	134	60	0,85	6,09	82	96	104	121
4/623	4	693	623	134	60	1,09	7,3	99	115	125	145
4/813	4	883	813	134	60	1,32	9,89	120	140	152	177
5/623	5	695	623	170	60	1,37	10,11	120	139	151	176
5/813	5	885	813	170	60	1,74	12,51	146	170	185	215

RIDEM PLUS STYLE

MODEL	DIMENSIONS (mm)					WATER CONTENT (L)	WEIGHT (KG)	Δt 50		Δt 60	
	COLUMNS	A HEIGHT	B TAPPING CENTERS	C DEPTH	D WIDTH			Kcal/h	watts	Kcal/h	watts
3/500	3	565	500	92	60	0,65	4,3	66	77	84	97
3/623	3	692	623	92	60	0,72	5,09	78	91	99	115
3/813	3	878	813	92	60	0,99	6,63	96	112	122	142
4/500	4	565	500	130	60	0,76	5,55	82	96	104	121
4/623	4	692	623	130	60	0,98	6,49	99	115	125	145
4/813	4	878	813	130	60	1,19	8,34	120	140	152	177

RIDEM BUDGET STYLE

MODEL	DIMENSIONS (mm)					WATER CONTENT (L)	WEIGHT (KG)	Δt 50		Δt 60	
	COLUMNS	A HEIGHT	B TAPPING CENTERS	C DEPTH	D WIDTH			Kcal/h	watts	Kcal/h	watts
WING 3/500	3	567	500	96	60	0,53	3,6	62	71	78	91
WING 3/623	3	690	623	96	60	0,62	4,6	74	85	94	109
WING 4/623	4	690	623	132	60	0,83	5,6	91	105	115	133

HISTORIC STYLE



MODEL	COLUMNS	A HEIGHT	B TAPPING CENTERS	C DEPTH	D WIDTH	WATER CONTENT (L)	WEIGHT (KG)	Δt 50		Δt 60	
								Kcal/h	watts	Kcal/h	watts
350/180	2	445	350	183	76	1,9	7,5	95	110	120	140
350/180 WITH FEET	2	510	350	183	76	1,9	8,6	95	110	120	140
500/180	2	595	500	183	76	2,26	9,95	111	130	141	163
500/180 WITH FEET	2	661	500	183	76	2,26	10,4	111	130	141	163
600/180	2	695	600	183	76	2,52	10,65	122	143	154	180
600/180 WITH FEET	2	760	600	183	76	2,52	11,5	122	143	154	180
800/180	2	890	795	183	76	3,28	12,2	143	168	181	211
800/180 WITH FEET	2	955	795	183	76	3,28	13,35	143	168	181	211

RETRO STYLE



MODEL	DIMENSIONS (mm)					WATER CONTENT (L)	WEIGHT (KG)	Δt 50		Δt 60	
	COLUMNS	A HEIGHT	B TAPPING CENTERS	C DEPTH	D WIDTH			Kcal/h	watts	Kcal/h	watts
600/220	3	713	600	226	78	3,05	12,78	163	190	206	240
600/220 WITH FEET	3	768	600	226	78	3,05	13,61	163	190	206	240
800/220	3	907	795	226	78	3,5	17,78	190	221	241	280
800/220 WITH FEET	3	961	795	226	78	3,5	18,61	190	221	241	280

GNB DIŐ TİC. LTD. ŐTİ.
Çamlık Mah. Őehit Burak Kurtuluő Cad.
Uęurlu Sok. No: 67 K: 2 D: 6 İstanbul TURKEY
Tel: + 90 216 415 39 66
Fax: + 90 216 415 39 88
E-mail: info@gnb.com.tr
"GNB: Your Heat Partner in Turkey"

www.gnb.com.tr

